


E60 SERIES PRO-STYLE RANGE HOOD



For domestic cooking only.

Styling is fresh and modern, yet designed to easily complement popular pro-style, high performance cooking products.

A complete installation requires several optional components. Refer to page 2 when planning your installation

FEATURES

HOOD:

- Widths - 30" to 48" in 6" increments
- Stainless steel, 22 gauge, type 430, #4 brush
- Stainless steel baffle filters with handles - easily accessible, dishwasher safe
- 2-level cooktop lighting (30" & 36" wide hoods = 2 lamps, 42" & 48" wide hoods = 3 lamps. Uses 50W, GU10 halogen lamps. Bulbs not included.)
- Solid-State, infinite speed blower control with speed memory
- Exclusive, Broan Heat Sentry™ turns blower ON to HIGH speed when excess heat is detected
- 3/4" x 10" ducting - single blower (600 cfm)
- 4 1/2" x 18 1/2" ducting - dual blower (1200 cfm)
- For indoor use only.

NON-DUCTED RECIRCULATING KIT:

- ANKE60 Series (Optional)
- Stainless steel, 22 gauge, type 430, #4 brush
 - Available for hood widths up to 48"
 - Charcoal filters included
- Replacement charcoal filters:
- Service Part # SV08343 - round filter retail pack

BACKSPLASH:

- RMP Series (Optional)
- Widths - 30" to 48" in 6" increments
 - Stainless steel, 22 gauge, type 430, #4 brush - protects back wall and wipes clean easily
 - Two, removable, dual-position condiment storage shelves

SOFFIT CHIMNEY:

- AEE Series (Optional)
- Widths - 30" to 48" in 6" increments
 - Stainless steel, 22 gauge, type 430, #4 brush
 - Recommended for use when installation location has no soffit

SPECIFICATION:


Single Blower

- 120 VAC, 60 Hz, 5.5 Amps
- 600 cfm, sound level no greater than 13.5 sones (high speed, vert. & horiz. discharge)
- 150 cfm, 1.5 sones (working speed, vert. & horiz. discharge)

Dual Blower

- 120 VAC, 60 Hz, 9.0 Amps
- 1200 cfm, sound level no greater than 14.5 sones (high speed, vert. & horiz. discharge)
- 350 cfm, 2.0 sones (working speed, vert. & horiz. discharge)

Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711
Broan-NuTone Canada Mississauga, Ontario www.broan.ca 877-896-1119





Models
E6030SS
E6036SS

Models
E6042TSS
E6048TSS



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

RMP Series Backsplash (Optional)



AEE Series
Soffit Chimney
(Optional)

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted By Date

E60 SERIES RANGE HOOD SYSTEM

INTERNAL BLOWERS

