

Chill® Premier Smart Room Air Conditioners

SPECIFICATIONS

★ENERGY STAR® models

Model	UPC	Cooling Btu	Heating Btu	Volts Rated	Cooling Amps	Cooling Watts	EER	CEER	Estimated Yearly Energy Cost	Moisture Removal-Pints/HR	Refrigerant	CFM	Wt. Net/Ship Lbs.
FIXED CHASSIS, COOL ONLY (WINDOW INSTALLATION ONLY)													
★ CCF05A10A		5200	—	115	4.3	459	12.1	12.1	\$41	1.0	R410A	141	44/51
★ CCF06A10A		6000	—	115	4.3	492	12.1	12.1	\$45	0.9	R410A	141	44/51
★ CCF08A10A		8000	—	115	5.8	661	12.1	12.0	\$60	1.0	R410A	206	51/57
★ CCF10A10A		10000	—	115	7.3	826	12.1	12.0	\$75	1.2	R410A	282	64/73
★ CCF12A10A		12000	—	115	8.6	992	12.1	12.0	\$90	1.5	R410A	270	73/82
SLIDE OUT CHASSIS, COOL ONLY													
★ CCW06B10A		6000	—	115	4.3	492	12.2	12.1	\$44	0.9	R410A	200	44/51
★ CCW08B10A		8000	—	115	5.8	661	12.1	12.0	\$60	1.0	R410A	250	44/61
★ CCW10B10A		10000	—	115	7.3	826	12.1	12.0	\$74	1.2	R410A	300	51/68
★ CCW12B10A		12000	—	115	8.6	992	12.1	12.0	\$89	1.5	R410A	330	64/86
★ CCW15B10A		15000	—	115	11.0	1270	11.9	11.8	\$117	2.0	R410A	400	73/93
★ CCW18B30A		18000	—	230	7.1	1525	11.9	11.8	\$138	2.7	R410A	520	106/136
★ CCW24B30A		24000	—	230	10.2	2308	10.4	10.3	\$209	2.7	R410A	590	117/144
SLIDE OUT CHASSIS, HEAT & COOL													
CEW08B11A		8000	4200	115	6.3	670	11.0	10.9	\$61	2.1	R410A	250	44/61
CEW12B33A		12000	10600	230	4.8	1060	11.0	10.9	\$96	3.3	R410A	265	64/86
CEW18B33A		18000	10600	230	7.2	1600	10.8	10.7	\$144	5.5	R410A	430	106/136
CEW24B33A		24000	10600	230	10.6	2340	9.5	9.4	\$211	6.5	R410A	560	117/144



INSTALLATION

Model	Height Inches			Minimum Extension Into Room Inches	Minimum Extension Outside Inches	Window Width Inches		Carton Dimensions Inches		
	Height Inches	Width Inches	Depth Inches			Minimum*	Maximum	Height	Width	Depth
CCF05A10A, CCF06A10A	13 3/8	18 5/8	15 5/8	—	—	26	36	14 1/2	21 1/2	17 3/4
CCF08A10A	13 3/8	18 5/8	17 5/8	—	—	26	36	14 1/2	21 1/2	18 1/2
CCF10A10A, CCF12A10A	15 1/8	19 7/8	21 3/4	—	—	26	36	17 1/2	21 7/8	23 3/4
CCW06B10A, CCW08B10A, CEW08B11A, CCW10B10A, CCW12B10A, CEW12B33A	14 5/8	19 3/4	23 3/4	—	—	26	36	17	22	26
CCW15B10A, CCW18B30A, CEW18B33A	18	23 7/8	25 3/8	—	—	26	36	19 3/8	25 5/8	29 5/8
CCW24B30A, CEW24B33A	18 5/8	27	26 5/8	—	—	26	36	19 1/2	29 1/4	31

All Chill Premier CCF models are designed for window installation only.

* Minimum widths achieved using one side curtain assembly as opposed to both in a standard installation.

CIRCUIT RATING/BREAKER

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
ALL CCF MODELS, CCW06B10A, CCW08B10A, CCW10B10A, CCW12B10A, CEW08B11A	125V-15A	5-15P	6	
CCW15B10A			5.5	
CCW18B30A, CCW24B30A	250V-20A	6-20P	4	
CEW12B33A, CEW18B33A, CEW24B33A			6	

