



Stainless Frame



Black Frame



Integrated Frame



Integrated Solid

Additional Options

- Stainless lock model available




Stainless Lock Model

Key Features

- Convection cooling system provides a quick cool down and consistent temperature
- Extended lower interior maximizes storage options
- Black interior
- LowE coated, argon gas filled, dual thermopane glass door provides protection from harmful UV Light
- Stainless steel full-wrap door and handle (7/8" diameter)
- Stainless steel grille (stainless model), black metal grille (black & integrated models)
- Five, three-quarter extension, black wine racks
- Digital touch pad control
- Temperature range: 34°F to 60°F
- Bright white LED lighting
- Volume of 5.5 cu ft holds up to 48 wine bottles (750 ml)
- Field reversible door is shipped right-hand hinged
- Integrated model requires 3/4" custom door panel and handle (not supplied by U-Line)
- Built-in or freestanding
- Four adjustable leveling legs

Model Details


Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UHWC124-SG01A	115 / 60	Field Reversible	Stainless Frame	125 lb
UHWC124-SG31A	115 / 60	Field Reversible	Stainless Frame (Lock)	125 lb
UHWC124-IG01A	115 / 60	Field Reversible	Integrated Frame	115 lb
UHWC124-IS01A	115 / 60	Field Reversible	Integrated Solid	110 lb
UHWC124-BG01A	115 / 60	Field Reversible	Black Frame	125 lb




Specifications

Model	HWC124
Amps: Running (115 v)	1.2 A
Capacity: Wine Bottle (750 ml)	48
Capacity: Volume (cu ft)	5.5
Dimensions: Product Depth	22 1/2" / 572 mm
Dimensions: Product Height	34 1/8" / 867 mm
Dimensions: Product Width	23 15/16" / 608 mm
ENERGY STAR (Glass)	No
ENERGY STAR (Solid)	Tier 3
Energy Consumption: Avg. Per Year	310 kWh
Panel Height	30 1/4" / 768 mm
Panel Thickness	3/4" / 20 mm
Panel Type	2 3/4" / 70 mm Frame or Solid Panel
Panel Width	23 3/4" / 603 mm
Refrigerant Type	R600a
Sabbath (Star K Certified)	Yes
Temperature Range	34°F to 60°F

Back



Cabinet Cut-Out



Warranty

- 1 Year (parts & labor) / 5 year sealed system (parts)
- + **Additional 1 Year (parts & labor) warranty at no cost with product registration**

See complete warranty for details



Installation Notes

- 24" cutout width sufficient if door protrudes beyond adjacent cabinetry
- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow



Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.